KITO

Lever Hoist
LB Model
Up to 9 t



The Original
Constantly developed further and improved



- **Unique freewheel chain adjusting mechanism** with safeguards against accidental freewheeling under load
- **Rugged lever handle**
- **Smooth geared mechanism** for effortless handling
- **Light and compact**

Made in Japan!



www.kito.net

Kito Europe GmbH
Heerdter Lohweg 93
D-40549 Düsseldorf
Tel. + 49 (0) 211 - 52 80 09 - 0
Fax + 49 (0) 211 - 52 80 09 - 59
info@kito.net
www.kito.net

KITO HOISTS
Always on the safe side



Hook latch with safety tip

KITO Original freewheel chain adjusting mechanism protects from accidental freewheeling

Nickel plated load chain grade 100 (V) (1000 N/mm²), in accordance with standard EN 818-7

Fourfold riveted increased safety



Options:

Kito-Clip*



Point load hook
for special applications / e.g. in shipbuilding and in sheet metal forming



- **LB-OF** without freewheel chain adjusting mechanism
- **LB-OLL** with optional slip clutch

Technical data valid for all LB models *to be used for pulling horizontal loads only

Type	LB008	LB010	LB016	LB025	LB032	LB063	LB090
Capacity, kg	800	1000	1600	2500	3200	6300	9000
Standard lift, m	1,5	1,5	1,5	1,5	1,5	1,5	1,5
Hand pull to lift full load, daN	28,4	35,3	33,3	36,3	36,3	37,2	38,2
Load chain diameter, mm	5,6 x 15,7	5,6 x 15,7	7,1 x 19,9	8,8 x 24,6	10 x 28,0	10 x 28,0	10 x 28,0
Chain fall	1	1	1	1	1	2	3
Net weight, kg	5,7	5,9	8,0	11,2	15,0	26,0	40,0
Headroom C, mm	280	300	335	375	395	540	680
Weight for additional 1 m lift, kg	0,7	0,7	1,1	1,7	2,3	4,7	7,0

Disclaimer:
KITO does not assume liability for inappropriate usage of products.
Operating instructions must be followed at all times.
Subject to technical change, misprint and errors.

Contact
Kito Europe GmbH / Heerdter Lohweg 93 / D-40549 Düsseldorf
Tel. +49 (0) 211 / 52 80 09 - 0 / Fax +49 (0) 211 / 52 80 09 - 59
info@kito.net / www.kito.net